



UK Sampling Gauges Ltd

Building 1, Roman Bank, Bourne, Lincolnshire, PE10 9LQ, UK

Tel: +44 (0)1778 392818 Fax: +44 (0)1778 421169

E-mail: sales@samplinggauges.com

Web site: www.samplinggauges.com



Any-Level, Bottom Sampler ALBTMS 382 (St/St)

Applications

Our ALBTMS samplers combine the functions of two basic sampler types. They can be used to obtain spot samples from any level or depth within a liquid, to check for quality, density, or chemical purity, for example. They can also be used to obtain samples from the bottom (or at a specified distance from the bottom) of a tank or reservoir, to look for water underneath oil or fuel. They are ideally suited to taking samples from the fuel/water interface, to obtain evidence of microbial growth.

The ALBTMS sampler has two valves – one at the top, opened by a snatch on the supporting cable, the other at the bottom, opened by the protruding leg contacting the bottom of the tank or reservoir.

In operation, both valves stay closed (and the sampler therefore stays empty) until the sampler reaches the depth at which the sample is required. For this reason, you can be sure that true samples are obtained, uncontaminated and undiluted by liquid from any other level in the tank or reservoir.

Specifications

Overall diameter	38mm
Overall length	570mm
Weight (empty)	1.4kg
Bottom sampling range	1 to 12cm
Capacity	300ml
Material	316 Stainless Steel



ALBTMS 382

Spare parts available

“O” rings
Springs
Locking pins
Ball bearings



Please contact us if you require further information about these or other equipment offered by **UK Sampling Gauges Ltd**, or if you require equipment to be adapted or modified.