



# UK Sampling Gauges Ltd

Building 1, Roman Bank, Bourne, Lincolnshire, PE10 9LQ, UK

Tel: +44 (0)1778 392818 Fax: +44 (0)1778 421169

E-mail: sales@samplinggauges.com

Web site: www.samplinggauges.com



## Bottom Sampler BTMS 1002

### Applications

Our BTMS samplers provide the ideal tool for obtaining liquid samples from the bottom (or at a specified distance from the bottom) of a tank or reservoir. They are used to look for evidence of water underneath oil or fuel, for example, and can take samples from the fuel/water interface, for detecting microbial growth.

They can also be used to check the condition of the bottom of a tank, and to look for corrosion. They can be used to look for pollution in reservoirs or contamination in storage vessels.

In operation, the sampler remains sealed and empty as it is lowered into the liquid, until the "leg" contacts a solid surface (usually the bottom of the tank). The valve at the bottom of the sampler then opens, and the sampler fills. Air escapes through a non-return valve at the top of the sampler.

The protrusion of the leg can be adjusted, so that the sampler can take its sample from a predetermined height above the tank bottom.

As the sampler is lifted, the valve re-seals, ensuring that the sample is retained and not diluted on its way up through the liquid. The sampler therefore obtains true samples. It can take samples from any depth, as it is unaffected by outside pressure.



BTMS 1002

### Specifications

Overall diameter	64mm
Overall length (Leg retracted)	48cm
Sampler capacity	1 Litre
Weight	2.2kg
Material	316 Stainless Steel

The BTMS range also includes samplers that can be lowered through the vapour control valves on board oil tankers. Please contact us if you want further information about these or other equipment offered by **UK Sampling Gauges Ltd**, or if you require equipment to be adapted or modified.